## Ben O Digital Projector Specifications

## Benq

## MP721c

## **HIGHLIGHTS**

•	2200	<b>ANSI</b>	Lumens
---	------	-------------	--------

- XGA Native Resolution
- 2000:1 High Contrast Ratio
- Whisper Quiet 24 dB (Eco.
   Mode)
- Presentation Timer
- Panel Key Lock
- Blackboard Mode
- Power on/off Ring Tone
- Golden Ratio Color Wheel (5 Segments)
- "Q?" Hot Key for FAQ
- MyScreen
- Hot Key for "Mode" Selection
- 9 Sets of Application Mode
- Power saving "Auto Off"
- Security Password Function
- Resolution Reminder
- 4000 Hours Lamp Life (Eco. mode)
- HDTV Compatible (480p, 576p, 720p, 1080i)
- Wireless Module (optional)

otor Specifications				
Projection System	DLP <sup>TM</sup> technology by Texas	s Instruments®		
Panel	XGA DDR DMD <sup>TM</sup> x 1			
Native Resolution	XGA (1024 x 768)			
Brightness	2200 ANSI lumens			
Contrast Ratio	2000:1 (Full on/Full off)			
Aspect Ratio	4:3 Native, 16:9 Selectable			
Color	Full 16.7 million color palette			
Lens	F=2.6 to 2.77, f=20.4 to 23.5 mm			
Zoom Ratio	Manual Zoom, 1.15:1			
Image Size (Diagonal)	31" to 300"			
Throw Ratio	54"@6.6 feet(54"@2m)			
Lamp	200W, 3000/4000 hours (Normal/Economic mode)			
Computer Compatibility	VGA(640 x 350) to SXGA(1280 x 1024)			
HDTV Compatibility	480i, 480p, 576p, 720p, 1080i			
Video Compatibility	NTSC, PAL, SECAM			
Horizontal Frequency Vertical Scan Rate	31-82 kHz 48-85 Hz			
Vertical Scall Rate	Analog RGB: D-sub 15 pin x 1(shared)			
	PC DVI-I (shared with	1 '		
		D-sub 15 pin x 1(shared)		
Input Terminals	A/V S-Video: Mini Din			
1	Composite Video:			
	PC audio: Stereo n	nini jack x 1(shared)		
	Audio Video L/R audio: S	stereo mini jack x 1(shared)		
Output Terminal	PC Analog RGB: D-sub 15 pin x 1			
Output Terminar	Audio 2 Watt Speaker x 1			
Control Terminal	USB Connector : USB x 1, Type mini B			
	Serial Connector: RS232 8 pin MINI DIN			
Dimensions(W x H x D)	10.9 x 4 x 8.7 inches (278 x 100.3 x 220.2 mm)			
Weight Power Supply	5.9 lbs (2.67 kg)			
Power Consumption	100 to 240 VAC, 50 to 60 Hz			
Audible Noise	Max 285W 28/24 dB (Normal/Economic mode)			
Audioic Hoise	English/ French/ German/ It	,		
On-Screen Display	Traditional Chinese/ Simplified Chinese/ Japanese/			
Languages	Korean/ Swedish/ Dutch/ Turkish/ Czech/ Portuguese /			
	Thai/ Polish	C		
	PC Input:	A/V Input :		
	Dynamic	Dynamic		
Picture Modes	Presentation	Cinema		
11000101110000	sRGB	Standard		
	Cinema	Blackboard		
	Blackboard  Power on/off ring tone	Blackboard Mode		
	Power on/off ring tone Presentation Timer	Security Password		
	Panel Key Lock	Mute		
	Auto Adjustment	Auto Source Detection		
Functions	Freeze	HDTV Compatible		
	Blank (ECO mode)	Macintosh® Compatible		
	Auto Off	"Mode" Hot Key		
	Quick Cooling	"Q?" Hot Key for FAQ		
	Resolution Reminder	MyScreen (optional)		
	User's Manual	Soft Carry Case		
Aggregation (Ctandard)	Quick Start Guide	VGA Cable		
Accessories (Standard)	CD Manual Remote Control	PWR Cord Video Cable		
	Remote Control  Rattery for R/C	VIUCU CAUIC		

